
spuq Documentation

Release 0.1alpha

spuq Development Team

September 19, 2011

CONTENTS

1 Tutorial	3
1.1 First steps	3
2 Concepts	5
2.1 Bases and operators	5
3 Concept for the implementation of the residual based error estimator	7
3.1 Model setting	7
3.2 Algorithms	9
3.3 Data structures	10
3.4 Questions	12
4 Weblinks for development	13
4.1 Coding references	13
4.2 Scientific References	14
5 Package spuq.linalg	15
5.1 Basis	15
5.2 Vector	15
5.3 Operator	15
6 Indices and tables	17

Contents:

**CHAPTER
ONE**

TUTORIAL

1.1 First steps

Blah blah blah

CONCEPTS

2.1 Bases and operators

Bases and operators form the two closely related central concepts of spuq. This is for several reasons:

- Refinement of a basis: gives you a new basis and operators that restrict or project vectors from one basis to the other
- Operators on restricted base can be formed by composition of the operator with restriction or projection operator
- Many complicated bases as tensor product bases of simpler bases
- Forming of subbases, which is more or less coarsening
- Subbases of tensor product bases indexed by multiindex sets can give PCE bases
- Function bases: can be evaluated, can be orthogonalised via their Gram matrix, for TP bases via the tensor product of those matrices
- Simple construction: non-orthogonal basis with Gram matrix to orthogonal basis

Operators:

- Compositions can be formed efficiently
- Note that *efficiently* here means: if the vectors that the operators act on are large so that the significant portion of the runtime is spent in some matrix-vector operation

Advantages:

- a vector is not just a collection of numbers, you always know where what the numbers *mean*, since you always have the basis with it
- with the basis alongside you can compute norms in the real space instead of just the Euclidean
- you can restrict and project
- you cannot easily mess up since the operators check that the vectors come from their domain

2.1.1 Some mathematical notation

We have

$$H^1(\mathcal{D}; L_2(\Omega)) \simeq H^1(\mathcal{D}) \otimes L_2(\Omega) \quad (2.1)$$

where $H^1(\mathcal{D})$ is the Sobolev space ...

2.1.2 An example

Some demonstration of operator stuff:

```
A = FullLinearOperator( 1 + rand(3, 5) )
B = FullLinearOperator( 1 + rand(7, 3) )
print A.domain_dim(), A.codomain_dim()
print B.domain_dim(), B.codomain_dim()

x = FullVector( rand( 5,1 ) )
print x
```

Operators can be multiplied:

```
C = B * A
print C.domain_dim(), C.codomain_dim()
```

operator composition can be performed in a number of ways:

```
print B(A(x))
print (B * A)(x)
print B * A * x
print B * (A * x)
print (B * A) * x
```

similar as above, only as matrices:

```
print (B*A).as_matrix() * x.as_vector()
print B.as_matrix() * (A.as_matrix() * x.as_vector())
```

you can transpose (composed) operators:

```
AT=A.transpose()
BT=B.transpose()
CT=C.transpose()

y = FullVector( rand( CT.domain_dim(),1 ) )
print CT*y
print AT*(BT*y)
```

can add and subtract operators:

```
print (B * (A+A)) * x
print C*x+C*x
print (C-C) * x
print C*x-C*x
```

you can pre- and post-multiply vectors with scalars:

```
print 3*x-x*3
```

you can multiply operators with scalars or vectors with scalars:

```
print (3*C) * x
print (C*3) * x
print 3 * (C*x)
```

Note: This example was copied verbatim from test-zone/operators/test-operator-algebra.py

CONCEPT FOR THE IMPLEMENTATION OF THE RESIDUAL BASED ERROR ESTIMATOR

In this document all necessary formulas for the implementation of the residual-based a posteriori error estimator for the SGFEM method proposed by C. Gittelson and Ch. Schwab shall be collected.

Basic guidelines for this document

- all necessary formulas shall be collected, such that a complete workflow could be implemented from it
- math formulas should all be supplemented by code sketches
- the prose need not be nice, better complete

3.1 Model setting

Elliptic boundary value problem

$$-\nabla(a \cdot \nabla u) = f \text{ in } D \quad (3.1)$$

Homogeneous Dirichlet boundary conditions $u = 0$ on D

D is a Lipschitz domain. For the application we will restrict this to a rectangular domain, maybe simply $[0, 1]^2$, ok? Definition in FEniCS will look like:

```
# create mesh and define function space
mesh = UnitSquare(1, 1)
V = FunctionSpace(mesh, 'CG', 1)
```

3.1.1 Coefficient

The coefficient has the form

$$a(y, x) = \bar{a}(x) + \sum_{m=1}^M y_m a_m(x)$$

Note: How do we define the functions $a_m(x)$ on the FunctionSpace object \mathbb{V} in FEniCS how to we embed this into a spuq Basis object?

What kind of functions shall we take for the a_m first? Piecewise? Trigonometric? What about \bar{a} ? Constant?

Specification of the random variables y_m . Need to be defined on $[-1, 1]$ with $\#supp(y_m) = \infty$. Take simply uniform $U(-1, 1)$? Needs to be symmetric?

3.1.2 Operator

Continuous operator

$$\bar{A} = -\nabla \bar{a}(x) \cdot \nabla$$

$$\bar{\mathcal{A}} = \text{Id} \otimes \bar{A}$$

$$A_m = -\nabla a_m(x) \cdot \nabla$$

$$K_m = r(y) \mapsto r(y)y_m$$

$$\mathcal{A}_m = K_m \otimes A_m$$

$$\mathcal{A} = \bar{\mathcal{A}} + \sum_{m=1}^{\infty} \mathcal{A}_m \tag{3.2}$$

Discrete operator

For each μ we have some V_μ

solution has the form

$$w(y, x) = \sum_{\mu \in \Lambda} w_\mu(x) P_\mu(y)$$

ordered basis $B_\mu = \{b_{\mu,i}\}$ of V_μ

$$w(y, x) = \sum_{\mu \in \Lambda} \sum_{i=1}^{\#B_\mu} w_{\mu,i} b_{\mu,i}(x) P_\mu(y)$$

for each vector $w_\mu = [\dots w_{\mu,i} \dots]^T$ of length $\#B_\mu$ we discretise equation (3.2)

3.2 Algorithms

3.2.1 Solve algorithm

Solve algorithm:

```
def solve( eps, w0, eta0, chi ):
    w=w0; eta=eta0;
    for i in xrange(1,):
        [w,zeta]=pcg( w, chi*xi )
        (eta,eta_S)=error_estimator( w, zeta )
        if eta<=eps:
            return w
        w=refine(w,eta_S)
```

Identification of variables:

- $\text{eps} = \epsilon$, threshold for the total estimated error
- $w_0 = w_N^0$, initial solution, is a collection of multiindices with associated vectors that include the basis used for this multiindex; the parameter $\mathcal{V}^{1 or 0}$ is included in w_0
- $\chi_0 = \xi^0$ error bound of the initial solution (?), estimate $\xi^0 := (1 - \gamma)^{-1/2} \|f\|_{V^*}$ (see note 3)
- $\chi = \chi$ parameter that determines the accuracy of the solver; between 0 and 1 (exclusive)

Note: maybe we can pass ζ^0 instead of ξ^0 and compute ξ^0 using the error estimator, i.e. swapping lines 2 and 3 of the algorithm

Note: why does \mathcal{V} have a different index than w in the paper; should be the same

Note: we rename ξ to η ; further the error estimator returns also the local error, not only the global one

3.2.2 Error estimator

The function `error_estimator`:

```
def error_estimator( w, zeta, c_eta, c_Q ):
```

Projection $\Pi_\mu^\nu : V_\nu \rightarrow V_\mu$ for some $\mu, \nu \in \Lambda$ can be an arbitrary map such as the L^2 -projection, the \mathcal{A} -orthogonal projection or nodal interpolation

```
def project( ):
```

3.2.3 Refinement

3.2.4 PCG

This should be implemented as a standard preconditioned conjugate gradient solver, where the special treatment necessary for the peculiar structure of w_N is hidden in a generalised vector class that takes care of that.

Meaning of the variables

- $\rho = r$ residual
- $s = s$ preconditioned residual
- $v = v$ search direction
- $w = w$ solution
- ζ is the enery norm (w.r.t. \bar{A}) of the preconditioned residual s , i.e. $\|s\|_{\bar{A}}^2$

Algorithm:

```
def pcg( A, A_bar, w0, eps ):
    # use forgetful_vector for vectors
    w[0] = w0
    r[0] = f - apply(A, w[0])
    v[0] = solve(A_bar, r[0])
    zeta[0] = r[0].inner(s[0])
    for i in count(1):
        if zeta[i-1] <= eps**2:
            return (w[i-1], zeta[i-1])
        z[i-1] = apply(A, v[i-1])
        alpha[i-1] = z[i-1].inner(v[i-1])
        w[i] = w[i-1] + zeta[i-1] / alpha[i-1] * v[i-1]
        r[i] = r[i-1] - zeta[i-1] / alpha[i-1] * z[i-1]
        s[i] = solve(A_bar, r[i])
        zeta[i] = r[i].inner(s[i])
        v[i] = s[i] - zeta[i] / zeta[i-1] * v[i-1]
```

3.3 Data structures

3.3.1 Vectors

Sketch for the generalised vector class for w (we call it for now AdaptiveVector, proposals for a better name are welcome)

```
class AdaptiveVector(object):
    #map multiindex to Vector (=coefficients + basis)
    def __init__(self):
        self.mi2vec = dict()

    def extend( self, mi, vec ):
        self.mi2vec[mi] = vec

    def active_indices( self ):
        return self.mi2vec.keys()

    def get_vector( self, mi ):
        return self.mi2vec[mi]

    def __add__(self, other):
        assert self.active_indices() == other.active_indices()
        newvec = FooVector()
        for mi in self.active_indices():
            newvec.extend( mi, self.get_vector(mi)+other.get_vector(mi) )
        return newvec

    def __mul__():
```

```

    pass

def __sub__():
    pass

```

The AdaptiveVector needs a set of /normal/ vectors which represent a solution on a single FEM mesh:

```

class FEMVector(FullVector):
    INTERPOLATE = "interpolate"

    def __init__(self, coeff, basis):
        assert isinstance(basis, FEMBasis)
        self.FullVector.__init__(coeff, basis)

    def transfer(self, basis, type=FEMVector.INTERPOLATE):
        assert isinstance(basis, FEMBasis)
        newcoeff = FEMBasis.transfer(self.coeff, self.basis, basis, type)
        return FEMVector(newcoeff, basis)

```

The FEMVector's need a basis which should be fixed to a ``FEMBasis and derivatives (which could be a Fenics or Dolfin basis or whatever FEM software is underlying it):

```

class FEMBasis(FunctionBasis):
    def __init__(self, mesh):
        self.mesh = mesh

    def refine(self, faces):
        (newmesh, prolongate, restrict) = self.mesh.refine(faces)
        newbasis = FEMBasis(newmesh)
        prolop = Operator(prolongate, self, newbasis)
        restop = Operator(restrict, newbasis, self)
        return (newbasis, prolop, restop)

    @override
    def evaluate(self, x):
        # pass to dolfin
        pass

    @classmethod
    def transfer(coeff, oldbasis, newbasis, type):
        # let dolfin do the transfer according to type
        pass

```

The FEMBasis needs a mesh class for refinement and transfer of solutions from one mesh to another. This mesh shall have derived class that encapsulates specific Mesh classes (that come e.g. from Dolfin)

```

# in spuq.fem?
class FEMMesh(object):
    def refine(self, faces):
        return NotImplemented

# in spuq.adapters.fenics
class FenicsMesh(FEMMesh):
    def __init__(self):
        from dolfin import Mesh
        self.fenics_mesh = Mesh()

    def refine(self, faces):
        new_fenics_mesh = self.fenics_mesh.refine(faces)

```

```
prolongate = lambda x: fenics.project( x, fenics_mesh,
                                         new_fenics_mesh )
restrict = lambda x: fenics.project( x, new_fenics_mesh,
                                    fenics_mesh )
return (Mesh( new_fenics_mesh ), prolongate, restrict)
```

Refinement:

```
b0 = FEMBasis( FENiCSMesh() )
coeffs = whatever()
v0 = FEMVector( coeffs, b0 )
faces = marking_strategy( foo )
(b1, prol, rest) = b0.refine( faces )
v1 = prol( v0 )
assert v1.get_basis() == b1
assert v1.__class__ == v2.__class__
```

3.4 Questions

- Is Λ adaptively enlarged? Probably yes; we let it denote the set of *active* multiindices.
- What kind of requirements are there for the projectors Π_μ^ν ?

WEBLINKS FOR DEVELOPMENT

This file contains links that aid in the development of spuq. This should not be a general link collection but should only contain links that are often needed to look up stuff without asking google again and again for the same stuff. Links that are included should be:

4.1 Coding references

4.1.1 Programming resources

Python

Libraries

- numpy reference: <http://docs.scipy.org/doc/numpy/reference/>
- numpy user guide: <http://docs.scipy.org/doc/numpy/user/>
- scipy reference: <http://docs.scipy.org/doc/scipy/reference/>
- numpy/scipy cookbook: <http://www.scipy.org/Cookbook>
- Traits user manual: http://github.enthought.com/traits/traits_user_manual/index.html

4.1.2 Version control

- git resources from numpy: http://docs.scipy.org/doc/numpy/dev/gitwash/git_resources.html#git-resources
- git cheat sheet: <http://help.github.com/git-cheat-sheets/>
- the git book: <http://book.git-scm.com/index.html>

4.1.3 Writing documentation

Sphinx

- Sphinx: <http://sphinx.pocoo.org/contents.html>
- autodoc: <http://sphinx.pocoo.org/ext/autodoc.html>

reStructuredText

- Quickref: <http://docutils.sourceforge.net/docs/user/rst/quickref.html>
- Wikipedia: <http://en.wikipedia.org/wiki/ReStructuredText>
- Wikipedia.de: <http://de.wikipedia.org/wiki/ReStructuredText>
- Emacs mode: <http://docutils.sourceforge.net/docs/user/emacs.html>

4.2 Scientific References

4.2.1 Quadrature

4.2.2 Orthogonal polynomials

PACKAGE SPUQ.LINALG

The basic linear algebra classes of spuq, abstracting the concepts of bases, vectors, and operators.

5.1 Basis

5.2 Vector

5.3 Operator

INDICES AND TABLES

- *genindex*
- *modindex*
- *search*